

Production of propylene from methanol via two-stage catalytic dimethyl ether conversion, introduces dimethyl ether, vapor and steam into reactors containing shape-selective catalyst

Patent Number: DE10027159
Publication date: 2001-12-13
Inventor(s): KOSS ULRICH (DE); KOENIG PETER (DE); HOLTSMANN HANS-DIETER (DE); ROTHAEML MARTIN (DE)
Applicant(s): MG TECHNOLOGIES AG (DE)
Requested Patent: ☐ DE10027159
Application Number: DE20001027159 20000531
Priority Number (s): DE20001027159 20000531
IPC Classification: C07C1/20; C07C11/06
EC Classification: C07C1/20, C07C11/06
Equivalents:

Abstract

The stereo-selective catalyst of zeolite, packs vertical reactors in series. A side stream of dimethyl ether (DME)-containing vapor and steam forms a product stream which is extracted and sent to a second reactor with a further side stream of DME/vapor/steam mixture. From the last reactor in the sequence, product mixture is extracted and cooled. A propane-rich fraction is separated. Some residue is recycled. The stereo-selective catalyst of zeolite, packs vertical reactors in series. A side stream of DME-containing vapor and steam, passed into the first reactor, forms a product stream which is extracted and sent to the second reactor, together with a further side stream of DME/vapor/steam mixture. From the last reactor in the sequence, product mixture is extracted and cooled. A propane-rich fraction is separated. The residue, partially gaseous, contains C3+ hydrocarbons. At least some residue is recycled to one or more reactors.

Data supplied from the esp@cenet database - I2